

**Same Swing Pair Opening - Controlled Ingress (Access Control) w/ Active Latching - 90° x 90° Swing  
XT/PX/LX Series x Electrified Entry Lever**

2 ea	Continuous Hinge w/thru-wire transfer	EMA-EA12	628	Syntégra
2 ea	Flush Exit Device x Electrified Lever, <b>or</b> Pushpad Device x Electrified Lever, <b>or</b> Lever x Electrified Lever	XT-L-ELS, <b>or</b> PX-L-ELS, <b>or</b> LX-ELS	628	Syntégra
2 ea	Mortise Cylinder (As Required)			By Others
2 ea	Surface Closer – Tri-Pack, Grade 1, 1-6 adjustable	CLSC16	689	Syntégra
1 ea	Power Supply – 24VDC, Single I/O	PS210	N/A	Syntégra
1 set	Perimeter and Edge Smoke Seals	SS-B	BRZ	Syntégra
2 ea	Fire/Smoke Label (as req'd.)			Syntégra

Operation: Free egress with interior operator actuation. Ingress via credential (Keypad, Card Access, Biometric, etc.) or optional keyed cylinder.

Hardware finishes can be adjusted as required to match the design intent

EM Series Stainless Steel hinges can also be substituted as required