



This preparation is required for fire rated single doors only. Due to variations in door and frame placements, it is acceptable and advisable to prepare for the strike at the time of installation.



Strike Cover

Undercut: Varies

Door is factory prepared with 9/16" hole in line with frame preparation and includes preinstalled fire pin

| TOLERANCE UNLESS OTHERWISE SPECIFIED |          |         |
|--------------------------------------|----------|---------|
| UNIT                                 | ENGLISH  | METRIC  |
| FRACTIONS                            | ± 1/32   | ---     |
| .X                                   | ± .1     | ---     |
| .XX                                  | ± .01    | ± .25   |
| .XXX                                 | ± .005   | ± .12   |
| ANGLES                               | ± 1      | ± 1     |
|                                      | .010 TIR | .25 TIR |
|                                      | .005 TIR | .12 TIR |

THIS DRAWING REMAINS THE PROPERTY OF SYNTEGRA LLC. IT MUST BE KEPT CONFIDENTIAL AND EMPLOYED ONLY FOR THE PURPOSE FOR WHICH IT WAS ISSUED. UNAUTHORIZED USE, REPRODUCTION, DISCLOSURE OR RETENTION IS EXPRESSLY PROHIBITED. ALL PROPRIETARY AND MANUFACTURING RIGHTS RESERVED.

| DESIGN HISTORY         | DATE       |
|------------------------|------------|
| DRAWN BY<br>Alan Uyeda | 09/01/2020 |
| PROJECT ENGINEER       |            |



**Fire Pin Strike Template**

| SIZE  | DWG. NO. | REV                  |
|-------|----------|----------------------|
| B     | T3002    | D                    |
| SCALE | NTS      | DO NOT SCALE DRAWING |
| SHEET |          | 1 OF 1               |